THERMOBILE

mobile climate solutions

DESCRIPTION

Fabr.year: 2018

- 2nd hand
- Repaired

COOLMOBILE CR17



FEATURES

- Reduces the ambient temperature with a maximum of 12°C.
- The cooled air is transported through flexible hoses.
- CR-17 S is stackable and framed without wheels.
- Plug and play as of 20°C outside temperature.
- Automatic operation with external thermostat.
- All models are supplied with forklift slots.
- Outdoor model cooling system, monoblock.
- Heating function allows a maximum of 7°C temperature increase.
- CR-17 M supplied with wheels.

ADVANTAGES

- Reduces the humidity when recirculated air from inside is being cooled down.
- The entire unit is located outside and therefore saves inside
- Transport of cooled air through flexible hoses.

APPLICATIONS

Cooling of tents, showrooms or field hospitals.

WORKING PRINCIPLE

The Coolmobile has a heatpumpsystem with a reverse setting for heating (only types CR-17 and CR-34).

TECHNICAL SPECIFICATIONS

COOLMOBILE CR SERIES	C-8	CR-17 M	CR-17 S	CR-34
Cooling capacity (kW)	8,2	17	17	32,8
Heating capacity (kW)	-	20	20	37,7
Airflow (m³/u)	1500	3500	3500	7000
Power consumption (A)	13,0	13,7	13,7	27,5
Voltage (V/ph/Hz)	230/1/50	400/3/50	400/3/50	400/3/50
Refrigerant type	R410A	R410A	R410A	R410A
Air outlet cone Ø (mm)	300	500	500	2x500
Air inlet cone ∅ (mm)	300	500	500	2x500
Thermostat connection	~	~	~	~
Dimensions (L*W*H) cm	170x90x115	180x120x140	173x111x144	225x120x205
Weight (kg)	200kg	305kg	305kg	600kg